

Accessories & Other Equipment

Auto Self-Cleaning Kit for threaded pH & ORP Probes

Ordering Code	Description
PRC-SM1-1/2	Auto Cleaning kit for 1/2" Threaded submersible probes
PRC-SM1-3/4	Auto Cleaning kit for 3/4" Threaded submersible probes,

Note: Instalallation on mains water only by licensed plumber with approved back-flow preventor valve

Description

Auto Cleaning kit for 1/2" Threaded submersible probes, includes grey PVC Probe Washer, 20m of 1/4" PE tubing & 1/4" 240VAC N/C Solenoid Valve. OPTIONAL ITEMS: pH or ORP Probe, Submersible Probe Holder & Cyclical Timer

Common applications include Cleaning of Probes used in submersible wastewater applications



- Suitable for water or air cleaning
- 1/4" Hose cleaning connection, with 1/4" BSP Solenoid valve
- 240Vac Solenoid Valve, 10 Bar Max Pressure, 10mm Orifice

Optional Probe Holders

Ordering Code	Description
PRH-SM1-100	Submersible Probe Holder, Length= 100cm
PRH-SM2-100	Submersible Probe Holder with M40 Compression Gland

Optional Cyclic Timer

Ordering Code	Description
PRC-SM1-TIMER	Cyclical Timer that fits onto DIN plug of PRC-SM1 Auto Probe Cleaner kits (Clean time adjustable 0.5 to 10 seconds, Interval time adjustable 0.5 to 45 minutes), IP65

Common Compatible Probes

Ordering Code	Description
WA OPF10-NNN10	General purpose pH Sensor, single junction, 1/2 MNPT extra algecide, 10ft cable BNC, 6.9 bar at 80 Deg C max, M-10-A (I 1004, M-10-A-PH). Submersible only with optional probe holder.
WA OPF10-PBN10	General purpose single junction platinum ORP probe, ½" NPT, 10 ft BNC, 6.9 bar at 80 Deg C max. (I 1005, M-10-ORP-A). Submersible only with optional probe holder.
WA M-11-HpH	Double junction pH probe HipH, screw-in 3/4" MNPT industrial type 15 ft cable BNC (I 1100, M-11-HpH). Submersible only with optional probe holder.
WA OPF11-PB11B2	M-11-ORP-HiAll Double junction platinum ORP probe, 0-110 degC, 10.3 bar max, 3/4" MNPT industrial use, 15ft cable BNC (I 1131, M-11-ORP-HT). Submersible only with optional probe holder.
WA M-12-HpH	Double junction pH sensor, screw-in 3/4" MNPT industrial use, withdrawn bulb, concave end for high flow or for easy cleaning, 15ft cable BNC (I 1200, M-12-HpH). Submersible only with optional probe holder.
WA M-12-FLAT	Double junction pH sensor, screw-in 3/4" MNPT industrial use, Flat bulb, Flat end for high flow or for easy cleaning, 15ft cable BNC (I 1205, M-12-FLAT). Submersible only with optional probe holder.

