# MULTIPLE APPLICATIONS

WITH COMPACT PUMP



**Fixed Speed** 

The Econ FX and Econ VX are ideal for light duty applications in swimming pools, food & beverage, metal finishing, irrigation & horticulture and more.

# **Effortless Tube Replacement**



The patented quick release pump head includes a solid one piece tube construction.



**Variable Speed** 

Adjustable 8:1

- · Internal power supply
- · Wall mountable
- · cULus for indoor/outdoor use
- · CE listed

- Self-priming to 25 feet (7.6 m)
- Can run dry
- Output reproducibility ± 5%
- 4 lbs (1.8 kg)
- 5.2 x 4.4 x 5.9 in. (13.2 x 9.1 x 14.9 cm)

## **Optional mounting accessories sold separately**



**Mounting Kit EC303** For Stenner Tank or wall mount.



Stand EC304 For horizontal display or wall mount.

# **Econ FX Outputs**

E20FXB B White 24.8 25 93.7 1.7   E20FXC C White 38.8 25 146.7 1.7	Item Number Prefix	Pump Tube	Roller Assembly	Gallons per Day	Pressure psi	Liters per Day	Pressure bar
E20FXB B White 24.8 25 93.7 1.7   E20FXC C White 38.8 25 146.7 1.7	E10FXA	Α	White	7.4	25	28.0	1.7
<b>E20FXC</b> C White 38.8 25 146.7 1.7	E10FXB	В	White	14.0	25	52.9	1.7
	E20FXB	В	White	24.8	25	93.7	1.7
<b>E10FXH</b> H Black 14.0 80 52.9 5.5	E20FXC	С	White	38.8	25	146.7	1.7
	E10FXH	Н	Black	14.0	80	52.9	5.5
<b>E20FXH</b> H Black 23.5 80 88.8 5.5	E20FXH	Н	Black	23.5	80	88.8	5.5

Approximate Maximum Outputs @ 50/60Hz

# **Econ VX Outputs**

Item Number Prefix		Roller Assembly	Turndown Ratio	Gallons I per Day	Pressure psi	Liters per Day	Pressure bar
E10VXA	Α	White	8:1	0.8 to 7.4	25	3.0 to 28.0	1.7
E10VXB	В	White	8:1	1.2 to 14.0	25	4.5 to 52.9	1.7
E20VXB	В	White	8:1	1.6 to 24.8	25	6.0 to 93.7	1.7
E20VXC	С	White	8:1	4.4 to 38.8	25	16.6 to 146.7	1.7
E10VXH	Н	Black	8:1	1.7 to 14.0	80	6.4 to 52.9	5.5
E20VXH	Н	Black	8:1	2.7 to 23.5	80	10.2 to 88.8	5.5

Approximate Outputs @ 50/60Hz

# **Build An Item Number for the Pump or Tank System**

from output chart above

**Select Item Number Prefix** 

Omit if not ordering a Tank System

#### **Tank**

**\$7G** 7.5-Gallon UV Gray

\$7N 7.5-Gallon White

**\$1G** 15-Gallon UV Gray

\$1N 15-Gallon White

**S3G** 30-Gallon UV Gray

S3N 30-Gallon White

NOTE: Tanks also sold separately.

### **Voltage & Hertz/Cord**

A 120V 60Hz

**C** 230V 50Hz; CE plug

### **Suction & Discharge Tubing**

1 1/4" White

2 1/4" UV Black

**5** 6 mm White *Europe* 

### **Tube Material**

**S** Santoprene®

NOTE: Refer to chemical resistance guide for chemical compatibility.

This information is not intended for specific application purposes. Stenner Pump Company reserves the right to make changes to prices, products, and specifications at any time without prior notice.

FEFXVX 0415

